





**KANO LABORATORIES, INC.**  
**SAFETY DATA SHEET**

**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**Manufacturer:** Kano Laboratories, Inc.  
1000 E. Thompson Lane  
Nashville, TN 37211  
**Information Phone Number:** (615) 833-4101  
**Fax:** (615) 833-5790 **Emergency:** 800-424-9300 (Chemtrec)  
**Website:** www.kanolaboratories.com

HMIS Hazard Rating

	HEALTH	1
	FLAMMABILITY	2
	REACTIVITY	0
	PERSONAL PROTECTION	X

**Product Name:** PREVOX  
**MSDS Date of Preparation:** 12/15/2010  
**Product Use:** Industrial Rust Proof Coating

**SECTION 2: HAZARDS IDENTIFICATION**

Cloudy liquid with a solvent odor.

**EMERGENCY OVERVIEW**

**WARNING!** Combustible Liquid and Vapor. May cause eye and skin irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects such as headache, dizziness, nausea and vomiting. Harmful or fatal if swallowed. Aspiration into the lungs during ingestion or vomiting may cause lung damage.

**Potential Health Effects:**

**Eye:** May cause mild eye irritation with redness, tearing and stinging.

**Skin:** May cause mild irritation with redness and swelling. Prolonged or repeated contact may result in defatting and dermatitis.

**Inhalation:** Inhalation of vapors or mists may cause mucous membrane and upper respiratory tract irritation and central nervous system depression. Symptoms may include coughing, sore throat, shortness of breath, headache, dizziness, drowsiness, nausea, vomiting and unconsciousness.

**Ingestion:** Swallowing may cause gastrointestinal irritation with abdominal pain, nausea, vomiting and diarrhea and central nervous system depression with symptoms including headache and dizziness. Aspiration into the lungs during ingestion or vomiting may cause lung damage.

**Chronic Hazards:** Prolonged or repeated exposure may cause damage to the kidneys based on studies with laboratory animals.

**Carcinogen Status:** None of the components of this product at greater than 0.1% are listed as carcinogens by OSHA, IARC or NTP.

**Medical Conditions Aggravated by Exposure:** Pre-existing eye, skin, respiratory and kidney disorders.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	%
Aliphatic Petroleum Distillate	8052-41-3	60-90
Severely Hydrotreated Petroleum Distillates	64742-48-9/64742-54-7	10-20
Non-Hazardous Ingredients	Proprietary	5-15

**SECTION 4: FIRST AID MEASURES**

**Eye:** Rinse thoroughly with water for at least 15 minutes, holding the eye lids open to be sure the material is washed out. Get immediate medical attention.

**Skin:** Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use.

**Inhalation:** Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

**Ingestion:** DO NOT induce vomiting. Keep the victim calm and warm. Never give anything by mouth to an unconscious or drowsy person. Get immediate medical attention.

**SECTION 5: FIRE FIGHTING MEASURES**

**Flash Point:** 105°F (40.6°C) COC

**Flammable Limits:** LEL: 1.0%  
UEL: 6.0%

**Autoignition Temperature:** Not Determined

**Extinguishing Media:** Use carbon dioxide, dry chemical or foam. Water may be ineffective but can be used to cool containers and structures.

**Special Fire Fighting Procedures:** Wear NIOSH approved, positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

**Unusual Fire Hazards:** Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. Never use welding or cutting torch on or near containers (even empty) because product can ignite explosively. Combustion products may be hazardous.

**Hazardous Decomposition Products:** Oxides of carbon, organic compounds, formaldehyde smoke and fumes.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**Spill:** Remove all ignition sources such as open flames, spark producing equipment, pilot lights, etc. Wear appropriate protective clothing to prevent eye and skin contact including impervious gloves, safety goggles and respirator if needed (refer to Section 8 for specific recommendations). Ventilate area. Cover with an inert absorbent material and collect into an appropriate container for disposal. Report spills and releases as required to appropriate authorities.

**SECTION 7: HANDLING AND STORAGE**

**Handling:** Avoid breathing vapors, aerosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Wash exposed skin thoroughly with soap and water after use. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Keep containers closed when not in use. Do not cut, braze, solder, grind or weld empty containers. Do not reuse containers. Follow all MSDS precautions in handling empty containers.

**Storage:** Store in a cool, dry, well-ventilated location away from incompatible materials. Keep containers closed.

<b>SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION</b>
---

Chemical Name	Exposure Limits
Aliphatic Petroleum Distillate	100 ppm OSHA PEL-TWA 100 ppm ACGIH TLV-TWA
Severely Hydrotreated Petroleum Distillates	5 mg/m <sup>3</sup> OSHA PEL-TWA 5 mg/m <sup>3</sup> ACGIH TLV-TWA 10 mg/m <sup>3</sup> ACGIH TLV-STEL
Non-Hazardous Ingredients	None Established

**Ventilation:** Use with adequate general or local exhaust ventilation to maintain concentrations below the occupational exposure limits. Use explosion proof electrical equipment and wiring where required.

**Respiratory Protection:** If needed, a NIOSH approved respirator with organic vapor cartridges may be used. For higher exposures, a supplied air respirator may be required. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

**Skin Protection** Impervious gloves are recommended when needed to avoid skin contact. Based on available test data, 4H or Silver Shield gloves are suggested.

**Eye Protection:** Chemical safety goggles recommended.

**Other Protective Equipment:** Impervious clothing as required to prevent skin contact and contamination of personal clothing. Suitable eye wash and washing facilities should be available in the work area.

<b>SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES</b>
--

**Appearance and Odor:** Cloudy liquid with a solvent odor.

**pH:** Not applicable

**Boiling Point:** 325°F

**Vapor Pressure:** 1.7 mm Hg @ 25°C

**Vapor Density (air =1):** Greater than 1

**Specific Gravity:** 0.785

**Melting Point:** Not applicable

**Water Solubility:** Negligible

**Evaporation Rate (ether=1):** Less than 1

<b>SECTION 10: STABILITY AND REACTIVITY</b>
---

**Stability:** Stable under normal conditions of storage or use.

**Incompatibility/Conditions to Avoid:** Avoid strong oxidizing agents. Avoid heat, sparks, flames and all other sources of ignition.

**Hazardous Decomposition Products:** Combustion will produce oxides of carbon, organic compounds, formaldehyde, smoke and fumes.

**Hazardous Polymerization:** Will not occur.

<b>SECTION 11: TOXICOLOGICAL INFORMATION</b>
--

Toxicological testing has not been performed on this product as a mixture.

The calculated acute toxicity values, as determined by the DOT and other agency standard formula are: Oral LD50 = >2000; Dermal LD50 = >2000 mg/kg. Prevox is not classified as toxic under workplace or transportation criteria.

<b>SECTION 12: ECOLOGICAL INFORMATION</b>
---

No data available.

<b>SECTION 13: DISPOSAL INFORMATION</b>
---

Dispose in accordance with all local, state and federal regulations.

<b>SECTION 14: TRANSPORT INFORMATION</b>
--

**DOT Shipping Name:** Excepted from Hazmat when packaged in non-bulk containers (<119 gal) and shipped ground

**DOT Hazard Class/Packing Group:** None

**UN Number:** None

**DOT Labels Required (49CFR172.101):** None

**Hazardous Substance (49CFR172.101):** None

**Reportable Quantity:** Not applicable

**DOT Marine Pollutants:** This product does not contain marine pollutants as defined in 49CFR 171.8.

**IATA Shipping Name:** Petroleum Distillates

**IATA Hazard Class/Packing Group:** 3, III

**UN Number:** UN1268

**IATA Hazard Labels Required:** Class 3

<b>SECTION 15: REGULATORY INFORMATION</b>
---

**U.S. FEDERAL REGULATIONS:**

**CERCLA 103 Reportable Quantity:** Prevox is not subject to CERCLA release reporting, however, releases would be reportable as an oil spill. Many states have more stringent reporting requirements. Report spills and other releases as required under federal, state and local regulations.

**SARA TITLE III:**

**Hazard Category for Section 311/312:** Acute Health, Chronic Health, Fire Hazard

**Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

**Section 302 Extremely Hazardous Substances (TPQ):** None

**EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory.

<b>SECTION 16: OTHER INFORMATION</b>
--------------------------------------

**HMIS Ratings:** Health - 1

Flammability - 2

Reactivity - 0

**NFPA Ratings:** Health - 1

Flammability - 2

Reactivity - 0

=====

The information contained herein has been developed based upon current available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or the consequences of its use or misuse.